

**PONDICHERRY UNIVERSITY**  
**ENGINEERING WING**

**Er.N.SANKARAMOURTHY, B.E.,**  
EXECUTIVE ENGINEER

No.PU/EW/NIQ/2017-18/

Date: 31.07.2017

**NOTICE INVITING QUOTATIONS**

For and on behalf of Pondicherry University, Executive Engineer, Engineering wing, Pondicherry University invites sealed quotations from the eligible contractors for the work of “Maintenance and special repairs to the Canteen - II”. The rates should be filled in the schedule enclosed with this and placed in a sealed cover by superscribing the name of the work in the cover as mentioned above. An amount of Rs.2,500/- has to be furnished towards EMD which shall be in the form of demand draft from any one of the nationalized banks payable at Pondicherry, drawn in favour of the Finance officer, Pondicherry University. The notice with schedule can also be downloaded from the University website. [www.pondiuni.edu.in](http://www.pondiuni.edu.in)

The filled in quotation shall to be placed in the tender box kept in the reception counter at Dr.B.R.Ambedhkar Administrative Block, Pondicherry University. The quotations will be received up to 3.00 p.m. on 17.08.2017 and will be opened at 3.30 p.m. on the same day in the presence of tenderers those who present at the time of opening.

The Executive Engineer, Engineering wing, Pondicherry University reserves the right to accept or reject any or all quotation without assigning any reason thereof.

**EXECUTIVE ENGINEER**

**Encl: Schedule**

**PONDICHERRY UNIVERSITY**  
**ENGINEERING WING**

**SCHEDULE OF WORK**

Name of the work: Maintenance and special repairs to the Canteen - II

<b>S.No.</b>	<b>Description</b>	<b>Qty.</b>	<b>Rate Rs.P.</b>	<b>Unit</b>	<b>Amount Rs.P.</b>
1 14.42. 2	White washing with lime to give an even shade - Old work (one or more coats).	160.00		Sqm	
2 14.43	Removing white or colour wash by scrapping and sand papering and preparing the surface smooth including necessary repairs to scratches etc. complete.	300.00		Sqm	
3 13.43. 1	Applying one coat of cement primer of pproved brand and manufacture on wall surface - cement primer	300.00		Sqm	
4 13.26 A	Providing and applying ready mixed wall putty (JK / BIRLA ) of mm thickness over plastered surface to prepare the surface even and smooth complete	160.00		Sqm	
5 MR	Painting with plastic emulsion paint - commercial of approved brand and manufacture to give an even shade - two or more coats on old work.	430.00		Sqm	
6 15.2.2	Demolishing cement concrete manually / by mechanical means including disposal of material within 50 metres lead - 1:4:8 or leaner mix.	1.00		Cum	
7 11.3.1	Cement concrete flooring 1:2:4 (1 cement :2 coarse sand : 4 graded stone aggregate) finished with a floating coat of neat cement including cement slurry, but excluding the cost of nosing of steps etc. complete. 40mm thick with 20mm nominal size stone aggregate.	19.00		Sqm	
8 14.54. 1	Painting with synthetic enamel paint of approved brand and manufacture of required colour to give an even shade - One or more coats on old work.	140.00		Sqm	

9 16.10 0	Acid cleaning for the existing Mosaic floors, glazed tiles work and removing the stains and decays to give a glassy look etc complete (The acid used shall be 32% concentrated hydrochloric acid after taking on the precautionary measures)	65.00		Sqm	
10 9.119	Providing and fixing factory made P.V.C. door frame of size 50x47mm with a wall thickness of 5mm, made out of extruded 5mm rigid PVC foam sheet mitred at corners and joined with 2nos.of 150mm long brackets of 15x15mm M.S.square tube, the vertical door profiles to be reinforced with 19x19mm M.S.square tube of 19 gauge,EPDM rubber gasket weather seal to be provided through out the frame.The door frame to be fixed to the wall using M.S.screws of 65/100mm size complete as per manufacturers specification	20.00		Rmt	
11 9.120. 1	Providing and fixing to existing door frames - 30mm thick factory made solid panel PVC door shutter consisting of frame made out of M.S.tubes of 19 gauge thickness and size of 19mm x 19mm for stiles, top & bottom rails . M.S.frame shall have a coat of steel primers of approved make and manufacture M.S.frame covered with 5mm thick heat moulded PVC 'C channel of size 30mm thickness, 110mm width out of which 90mm shall be flat and 20mm shall be tapered in 45 drgree angle on either side forming stiles; and 5mm thick , 110mm wide PVC sheet out of which 90mm shall be flat and 20mm shall be tapered on the inner side to form top and bottom rail and 130mm wide PVC sheet out of which 90mm shall be flat and 20mm shall be tapered on both sides to form lock rail.Top bottom and lock rails shall be provided either side of the panel. 10mm(5mmx 2) thick ,	7.00		Sqm	

	<p>20mm wide cross PVC sheet shall be provided as gap insert for top rail &amp; bottom rail. Panelling of 5mm thick PVC sheet to be fitted in the M.S.frame welded/sealed to the stiles &amp; rails with 7mm (5mm + 2mm) thick x 15mm wide PVC sheet bending on inner side , and joined together with solvent cement adhesive. An additional 5mm thick PVC strip of 20mm width is to be stuck on the interior side of the 'C channel using PVC solvent adhesive etc.complete manufactures specification &amp; drawing.</p>				
	<b>Total</b>				

**Terms & Conditions:**

- i) The rates specified are firm and not subject to any variation.
- ii) The work should be completed within 30 days.
- iii) Payment will be made only after completion of the entire work.
- iv) The material should be got approved before commencement of work.
- v) Vat @ 3.5% will be deducted from the bill.

**Contractor**

**Executive Engineer**