

PONDICHERY UNIVERSITY
ENGINEERING WING

Er.N.SANKARAMOURTHY, B.E.,
EXECUTIVE ENGINEER

No.PU/EW/NIQ/2017-18/

Date: 24.07.2017

NOTICE INVITING QUOTATIONS

For and on behalf of Pondicherry University, Executive Engineer, Engineering wing, Pondicherry University invites sealed quotations from the eligible contractors for the work of “Replacing the damaged door shutters with frame at D-20 and repair works at E-12 quarters building”. The rates should be filled in the schedule enclosed with this and placed in a sealed cover by superscribing the name of the work in the cover as mentioned above. An amount of Rs.2,300/- has to be furnished towards EMD which shall be in the form of demand draft from any one of the nationalized banks payable at Pondicherry, drawn in favour of the Finance officer, Pondicherry University. The notice with schedule can also be downloaded from the University website. www.pondiuni.edu.in

The filled in quotation shall to be placed in the tender box kept in the reception counter at Dr.B.R.Ambedhkar Administrative Block, Pondicherry University. The quotations will be received up to 3.00 p.m. on 03.08.2017 and will be opened at 3.30 p.m. on the same day in the presence of tenderers those who present at the time of opening.

The Executive Engineer, Engineering wing, Pondicherry University reserves the right to accept or reject any or all quotation without assigning any reason thereof.

EXECUTIVE ENGINEER

Encl: Schedule

PONDICHERY UNIVERSITY
ENGINEERING WING

SCHEDULE OF WORK

Name of the work: Replacing the damaged door shutters with frame at D-20 and repair works at E-12 quarters building.

S.No.	Description	Qty.	Rate Rs.P.	Unit	Amount Rs.P.
1 15.13.1	Taking out doors, windows and clerestory window shutters (steel or wood) including stacking within 50m lead - Of area 3 sq. metre and below.	6		Each	
2 9.20.2	Providing and fixing ISI marked flush door shutters conforming to IS:2202 (Part 1) decorative type, core of block board construction with frame of 1 st class hard wood and well matched teak 3 ply veneering with vertical grains or cross bands and face veneers on both faces of shutters. - 30mm thick including ISI marked stainless steel butt hinges with necessary screws	6		Sqm	
3 13.50.1	Applying priming coat - with ready mixed pink or grey primer of approved brand and manufacture on wood work (hard and soft wood).	13		Sqm	
4 13.61.1	Painting with synthetic enamel paint of approved brand and manufacture to give an even shade - Two or more coats on new work.	16		Sqm	
5 9.100.1	Providing and fixing aluminium handles ISI marked anodised (anodic coating not less than grade AC 10 as per IS:1868)transparent or dyed to required colour or shade with necessary screws etc. complete :-125mm	6		Each	
6 9.97.3	Providing and fixing aluminium tower bolts ISI marked anodised (anodic coating not less than grade	3		Each	

	AC 10 as per IS:1868) transparent or dyed to required colour or shade with necessary screws etc. complete :- 200x10mm				
7 9.119	Providing and fixing factory made P.V.C. door frame of size 50x47mm with a wall thickness of 5mm, made out of extruded 5mm rigid PVC foam sheet mitred at corners and joined with 2nos.of 150mm long brackets of 15x15mm M.S.square tube, the vertical door profiles to be reinforced with 19x19mm M.S.square tube of 19 gauge, EPDM rubber gasket weather seal to be provided through out the frame. The door frame to be fixed to the wall using M.S.screws of 65/100mm size complete as per manufacturers specification	16		Mt.	
8 9.118.2	Providing and fixing to existing door frames - 30mm thick factory made (polyvinyl chloride) PVC door shutters made of styles and rails of a UPVC profile section of size 30x60mm and wall thickness 2mm +or- 0.2mm with inbuilt decorative moulding edging on one side. The styles and rails with plastic brackets of size 75x220mm metre and welded at the corners. The - stiles of the shutter reinforced by inserting galvanized M.S. tube of size 25x20mm and 1mm + or - 0.1mm wall thickness. The lock rail made up of 'H' section , a UPVC profile section of size 30mm x 100mm and 2mm + or - 0.2 wall thickness welded to the shutter style with a UPVC profile section single panel of size not less than 620mm,having overall thickness of 20mm and 1mm + or - 0.1mm wall thickness with 20mm panel beading of suitable size /	5		Sqm	

	glass (4mm thick plain glass) / louver section, louver frame of suitable size, as per manufactures specification. (For W.C. and bathroom door shutter)				
9 15.23.1	Dismantling tile work in floors and roofs laid in cement mortar including stacking material within 50m lead - For thickness of tiles above 10mm and upto 25mm.	7		Sqm	
10 11.37	Providing and laying ceramic glazed floor tiles 300X300mm (thickness to be specified by the manufacture) of 1st quality conforming to IS : 15622 of approved make (Bell / Johnson / Regency / Somany / Naveen / Asian) in colours such as white, ivory, grey, fume red, brown laid on 20mm thick cement mortar 1:4(1 cement : 4 Coarse sand) including pointing the joints with white cement and matching pigment etc., complete	7		Sqm	
11 15.2.2	Demolishing cement concrete manually / by mechanical means including disposal of material within 50 metres lead - 1:4:8 or leaner mix.	1		Cum	
12 4.1.10	Providing and laying in position cement concrete of specified grade excluding the cost of centering and shuttering.- All work upto plinth level -1:5:10 (1 cement:5coarse sand : 10 graded stone aggregate 40mm nominal size)	1		Cum	
13 17.13.2	Providing and fixing white vitreous china water closet squatting pan (Indian type) Orissa pattern WC pan of size 580 x 440 mm.	1		Each	
14 17.14.1	Extra for using coloured WC pan instead of white WC pan Orissa pattern WC pan 580 x 440 mm.	1		Each	
15 M.R	Providing and fixing PVC trap of 110mm dia including cost of cutting and making good wall and	3		Each	

	floors with necessary stiff cement concrete etc. The rate include cost of material and labour charges etc complete				
16 A.R	Providing and laying PVC pipe complete with PVC fittings including trenching and refitting etc for external work of 110mm dia (6kg/sqm) nominal bore.	3		Mt.	
17 18.58.1. 1	Providing and fixing PTMT grating of approved quality and colour circular type 100mm nominal dia.	3		Each	
18 A.R	Re-plastering or finishing the damaged cutting portion door side wall wherever required including paint finish etc.	1		Job	
19 4.1.3	Providing and laying in position cement concrete of specified grade excluding the cost of centering and shuttering.- All work upto plinth level -1:2:4 (1 cement:2coarse sand : 4 graded stone aggregate 20mm nominal size)	10		Cum	
20 5.9.1	Centring and shuttering including strutting, propping etc.and removal of form for: Foundations , footings, bases of columns ,etc. for mass concrete.- Using steel sheet with M.S.frames	7		Sqm	
21 11.13.1	Providing and fixing glass strips in joints of terrazo/ cement concrete floors. 40mmwide and 4mm thick.	31		Mt.	
	Total				

Terms & Conditions:

- i) The rates specified are firm and not subject to any variation.
- ii) The work should be completed within 30 days.
- iii) Payment will be made only after completion of the entire work.
- iv) The material should be got approved before commencement of work.
- v) Vat @ 3.5% will be deducted from the bill.

Contractor

Executive Engineer