	ENGINEERING WING						
Name of work: Providing aluminium partition at Department of Biochemistry &							
Molecular Biology							
	Schedule of work						
SI.No	Description	Qty Rate Unit Amount					
1	Code No: 15.23.2	Qty	Trato	0	Allount		
	Dismantling tile work in floors and roofs						
	laid in cement mortar including stacking						
	material within 50m lead - For thickness						
	of tiles above 25mm and upto 40mm.	6.00		Sqm			
2	Code No: 2.27						
	Supplying and filling in plinth with sand						
	under floors including, watering,						
	ramming consolidating and dressing	2.00		Cum			
3	Code No: 4.1.10			+			
	Providing and laying in position cement						
	concrete of specified grade excluding						
	the cost of centering and shuttering All						
	work upto plinth level -1:5:10 (1						
	cement:5coarse sand : 10 graded stone	0.25		Cum			
4	Code No: 6.4.2						
	Brick work with FPS bricks of class						
	designation 35 in superstructure above						
	plinth level upto floor V level in all shapes and sizes in cement mortar 1:6	0.10		Cum			
	shapes and sizes in cement monar 1.6	0.10		Cum			
5	Code No: 13.3.2						
	20mm cement plaster of mix cement						
	mortar 1:6 (1 cement : 6 fine sand)	3.00		Sqm			
6	Code No: 16.100						
	Acid cleaning for the existing Mosaic						
	floors, glazed tiles work and removing						
	the stains and decays to give a glassy						
	look etc complete (The acid used shall be 32% concentrated hydrochloric acid						
L		30.00		Sqm			
<u> </u>							
7	Analysis			+			
	Providing and laying fully vitrified floor tiles of size 60x60cm (thicknes to be						
	specified by the manufacturer) with						
	water absorption's less than 0.08% and						
	conforming to IS: 15622 of approved						
	make (Nitco / Rak / Johnson / Asian) in						
	all colors and shades, laid on approved						
	tile adhesive compound of 3mm thickin						
	including grouting the joints with white						
L	cement and matching pigments etc.,	27.00		Sqm			
8	Code No: 11.41.2B						

PONDICHERRY UNIVERSITY ENGINEERING WING

	Providing and laying Porcelint vitrified floor tiles of size 60x60cm (thicknes to be specified by the manufacturer) with water absorption's less than 0.08% and conforming to IS: 15622 of approved make (Nitco / Somany / Johnson / Asian) in all colors and shades, laid on 20mm thick cement mortar 1:4 (1			
	cement : 4 coarse sand) including		Carro	
	grouting the joints with white cement and	4.00	Sqm	
9	Code No: 21.1.1.1			
	Providing and fixing aluminimum work for doors, windows, ventilators and partitions with extruded built up standard tubular sections / appropriate Z sections and other sections of approved make conforming to IS : 733 and IS : 1285, fixed with rawl plugs and screws or with fixing clips, or with expansion hold fasteners including necessary filling up of gaps at junctions, at top, bottom and sides with required PVC / neoprene felt etc. Aluminimum sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminimum snap beading for glazing / panelling, C.P. brass / stainless steel screws, all complete as per architectural drawings. (Glazing and panelling to be paid for separately) : For fixed portion. Anodised	151.00	Kg	

10	Code No: 21.1.2.1			
	Providing and fixing aluminimum work			
	for doors, windows, ventilators and			
	partitions with extruded built up standard			
	tubular sections / appropriate Z sections			
	and other sections of approved make			
	conforming to IS: 733 and IS: 1285,			
	fixed with rawl plugs and screws or with			
	fixing clips, or with expansion hold			
	fasteners including necessary filling up			
	of gaps at junctions, at top, bottom and			
	sides with required PVC / neoprene felt			
	etc. Aluminimum sections shall be			
	smooth, rust free, straight, mitred and			
	jointed mechanically wherever required			
	including cleat angle, Aluminimum snap			
	beading for glazing / panelling, C.P.			
	brass / stainless steel screws, all			
	complete as per architectural drawings.			
	(Glazing and panelling to be paid for			
	separately) : For shutters of doors,			
	windows and ventilators including		IZ.	
	providing and fixing hinges / pivots and	42.06	 Kg	
11	Code No: 21.2.1			
	Providing and fixing 12mm thick			
	prelaminated particle board flat pressed			
	three layer or graded wood particle			
	board conforming to IS: 12823 grade 1			
	type II in panneling fixed in aluminimum			
	doors, windows, shutters and partition			
	frames with C.P. brass / stainless steel			
	screws etc., complete as per			
	architectural drawings. Prelaminated		0	
	particle board with decorative lamination	17.00	Sqm	
12	Code No: 21.3.2			
	Providing and fixing glazing in			
	aluminimum door, window, ventilator			
	shutters and partitions etc., with PVC /			
	neoprene gasket etc., complete as per			
	the architectural drawings. (cost of			
	aluminimum snap beading shall be paid			
	in basic item) : With float glass panes of	40.00	Sqm	
13	Code No: 21.3.1 + 2717a PSR 2009-10			
	Providing and fixing glazing in			
	aluminimum door, window, ventilator			
	shutters and partitions etc., with PVC /			
	neoprene gasket etc., complete as per			
	the architectural drawings. (cost of			
	aluminimum snap beading shall be paid			
	in basic item) : With float glass panes of	5	Sqm	

14	Code Nov 0.94			
14	Code No: 9.84 Providing and fixing IS:3564 make			
	Providing and fixing IS:3564 make aluminium extruded section body tubular			
	type universal hydraulic door closer with			
	double speed adjustment with necessary			
	accessories and screws			
		5.00	Nos	
15	Code No: 9.113			
15	Providing and fixing bright finished			
	100mm mortice lock with 6 levers			
	without pair of handles for aluminium			
	door with necessary screws etc	5.00	Nos	
		5.00	1103	
16	Code No: 9.100.1			
	Providing and fixing aluminium handles			
	ISI marked anodised (anodic coating not			
	less than grade as per 10 as per			
	IS:1868) transparent or dyed to required			
	colour or shade with necessary screws	5.00	Nos	
17	Code No: Non PSR			
	Providing and fixing gear wheel for			
	sliding door at aluminium "G" section of			
	40x40x20x20 by using 2nos. of gear			
	wheel and 3nos.of rubber bush for each	4.00	Nos	
18	Code No: 13.52.2			
	Finishing with epoxy paint (two or more			
	coats) at all locations prepared and			
	applied as per manufacturer			
	specifications including appropriate			
	priming coat, preparation of surface, etc.	52.50	Sqm	
19	Code No: 17.11.2			
	Providing and fixing white vitreous china			
	laboratory sink with number 3259.47 Cl			
	brackets CP brass chain with rubber			
	plug 40mm CP brass waste and 40mm			
	CP brass trap with necessary CP brass			
	unions complete including painting of			
	fittings and brackets cutting and making			
	good the walls wherever required size	2.00	Sqm	

I here by abide the rules and regulations stipulated in the CPWD form

Contractor

Executive Engineer